

Product Specification Data



Description

Rad Grafix Canvas is a 6mil film with an embossed canvas pattern. This film gives wall graphics character and adds dimension to a room. This film is removable and has a specially formulated microsphere acrylic adhesive which allows for great repositionability. Rad Grafix Canvas is adhered to a 90# lay flat liner. This film works well with eco-Solvent, Solvent, Latex and UV ink platforms.

Applications

Rad Grafix Embossed Canvas is designed to be applied to smooth interior walls. This product adheres best to painted walls with a flat, semi-gloss or floss paint finish. This film is not recommended for coated/sealed/treated stainless steel, brass or bronze surfaces.

Thickness

| | |
|----------|---------------|
| Film | 6 mil |
| Adhesive | .8 to 1.1 mil |
| Liner | 6.7 mil |

Dimensional Stability

Good

Adhesion

| | |
|------------------------|---------|
| To glass | 10oz/in |
| to standard test panel | 10ox/in |

Temperature Ranges

| | |
|---------------------------------|----------------|
| Minimum application temperature | 40°F |
| Service temperature range | -40°F to 200°F |

Removability

Removable for up to 1 year under normal circumstances

Storage Stability

1-year shelf life when stored at 70°F and 50% relative humidity

Product Series

RADC54100 54"x100'

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions of sale, including disclaimer of warranties and limitation of liability.